Re-measuring and Processing of the Israeli GNSS-Based 3-rd Level Geodetic Control Network

Dr. Yakov TUCHIN, Dr. Gilad EVEN-TZUR, Ms. Luba KAGANSKY, Ms. Marina KOZAKOV, Dr. Emanuel POLYAK, Ms. Einat SALMON and Dr. Gershon STEINBERG

1



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Re-measuring and Processing of the 3-rd Level Geodetic Control Network (G2)

- The levels of the Israeli coordinate system
- Selection of the points of the G2 class network
- Organization and description of the field measurements
- Processing
- · Preliminary adjustment

2



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



The levels of the Israeli coordinate system

According to the new Regulations, the Israeli National Grid will be based on the permanent GNSS stations. The primary class G is to be established and measured by Survey of Israel only.

It consists of 3 levels

3



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

The levels of the Israeli coordinate system

- G0 The array of 19 (to be extended up to 24) active permanent network stations (APN)
- G1 High accuracy network of 155 stations built specially for geodynamic monitoring
- G2 A network of about 1200 control points with easy access, at the density of about 1point per 20 sq km

4



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



The levels of the Israeli coordinate system Go – The array of 19 active permanent network stations

5



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

The levels of the Israeli coordinate system

G1 – High accuracy network of 155 stations built specially for geodynamic monitoring



6



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Selection of the points of the G2 class network

4 groups of G2 class points

• The first and the largest group (414 points) consists of the points constructed in 1994-2001 within the framework of the Undulation project and used as horizontal and vertical control points



7



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Selection of the points of the G2 class network

4 groups of G2 class points

 The second group comprises the layer of the control points used to base the GNSS projects made since 1998. These points (about 220) do not belong to the first group



8




FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Selection of the points of the G2 class network

4 groups of G2 class points

The third group (about 260 points) includes the benchmarks that could be used as base points for GNSS positioning



9



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Selection of the points of the G2 class network

4 groups of G2 class points

 The fourth group (about 200 new points) was created in order to condense the existing network



10



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Selection of the points of the G2 class network

4 groups of G2 class points



11



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Organization of the field measurements

The requirements for the receivers and measurements to minimize the possible errors

- Dual-frequency receivers with the p-code
- The occupation time at least 40 min (for baselines less than 5 km)
- The epoch interval equal 1 sec
- The baseline measured by two identical receivers with the same type of antenna
- The distance between the antenna and the receiver in the time of measurement was at least 3 meters

12



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Organization of the field measurements

- The inspection of the existing points was performed to estimate their physical condition
- The special set of maps was issued to back up the project
- Special type of log was developed to avoid errors in the recordings
- Special forms for each type of antenna were developed to minimize the errors of the measurements of the antenna height



13



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Organization of the field measurements

 The project of measuring about 1200 network points consists of 67 elementary units of work (loops). Each loop consists of about 30 points



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Description of the field measurements

- Each loop was measured by two receivers to provide uncorrelated loop closures
- Every station of the loop was determined from at least two occupations by means of two baselines
- The height of the antenna had to be changed at least once in different occupations of one station
- To connect the network to the high class stations, the stations G1 were observed (at least two in each loop).
- G1 class stations were connected to the G0 class APN stations

15



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Description of the field measurements

- The occupation time on the stations while measuring the baselines (at least):
 - Less than 5 km long 40 min
 - 5 to 10 km long 60 min
 - 10 to 20 km long about 120 min
 - More than 20 km 180 min and more
 - Occupation time on the G1 network stations had to be at least 90 min
- The measurements could not be performed if PDOP was greater than 4
- The cut off angle was 10 degrees

16



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Processing

- Processing was performed by means of the TTC program
- Each loop was processed separately
- Only double difference fixed solutions were accepted for further use (about 2000 baselines were processed)
- The processed baseline error does not exceed 3 mm
- Loop closure was less than 5mm + 1 ppm

17




FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Processing



	σX (mm)	σY (mm)	σZ (mm)
average for 279 baselines	1.6	1.5	1.4
standard deviation	0.6	0.5	0.5
minimal value	0.5	0.3	0.3
maximal value	3.7	3.0	3.2

Processing of the loop #28

Results of processing for the network segment (loops #28,29,33,41)

18



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



Preliminary adjustment of the network


- Each loop was adjusted separately as minimally constrained network with one fixed G0 station and the coordinate values of G1 stations were compared with the known ones
- Next step: connection of some loops into sub-network and adjustment of minimally constrained and fully constrained network
- The end step is to join the fragments into G2 network based on G0 and G1 class points

19



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009





Preliminary adjustment of the network

Results of the G1 and G2 class points adjustment. The G0 class points are constrained

Microsearch GeoLab, V2001.9.20.0						
2-D and 1-D Station Confidence Regions (95 percent):						
Order	Value	Semi_axis		Vertical		
		Major	Minor	v ei ticai		
G1: 19 points	average	0.013	0.011	0.015		
	max	0.018	0.016	0.023		
	min	0.006	0.006	0.006		
G2: 162 points	average	0.021	0.019	0.023		
	max	0.040	0.035	0.041		
	min	0.006	0.005	0.007		

21



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Preliminary adjustment of the network

Residuals of the coordinates of the G1 class points with respect to the constrained network adjustment

-0.021

Residuals of the coordinates of the G0/G1 class points with respect to the minimally constrained network adjustment

	Residuals (m)		
Name	Lattitude	Longitude	Ellipsoidal Height
BSHM	0.000	0.000	0.000
KATZ	0.005	-0.036	-0.022
CSAR	0.002	0.008	0.011
GILB	-0.002	0.008	-0.024
KABR	-0.005	0.015	0.004
ADMT	0.009	-0.013	0.015
ATLT	-0.007	0.000	0.017
AVTL	-0.008	-0.010	-0.011
BJAN	-0.013	-0.017	0.002
CABR	-0.017	-0.018	-0.008
CSON	-0.015	-0.011	-0.040
ECOV	-0.010	0.003	-0.020
GLON	-0.010	-0.012	-0.012
HZON	-0.008	-0.021	0.014
KRML	-0.002	-0.014	0.009
KRMV	-0.008	0.005	-0.006
KRTV	-0.010	-0.005	0.006
MRKA	-0.008	-0.008	-0.001
MTAT	0.003	0.010	0.020
NHRI	-0.012	-0.018	0.003
NTFA	-0.010	0.009	0.010
PARK	-0.002	0.008	-0.014
YAFI	-0.026	-0.017	-0.016

	YAFI -0.026 -0.0	7 -0.016	
average	-0.009	-0.008	-0.003
Std	0.008	0.012	0.015
Max	0.009	0.015	0.020
Min	-0.026	-0.036	-0.040

Min 22

average

Max





-0.026

FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009

-0.040







Conclusions

- The ultimate goal of the Survey of Israel is to define the cadastral boundaries with the accuracy of 5 cm at 95% level.
- To reach this goal the new national grid based on APN stations was established
- The new measurements and calculations project is on the way and will be completed by the end of 2009
- The field material analysis ensures that the quality of measurements is high enough to solve the problem of renewing national coordinate system

25



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009



05/05/2009

Thank you for your attention!

26



FIG Working Week 2009 Surveyors Key Role in Accelerated Development Eilat, Israel, 3 – 8 May, 2009

